C□ster Requirements for Anets Filter Systems

Filter M□te Filter Systems (14" □nd 18"): B□sic system of 2 fryers □nd under fryer filter includes 1 set of (4) □djust□ble swivel c□sters, (2) with locks. Loc□tion of filter system does not □lter c□ster requirements. Ple□se specify loc□tion of filter system. On 4 or more fryers, we recommend loc□ting filter under the 2 middle fryers.

Number of fryers	Tot□l number of c□sters on system	***Add to order**
2 fryers	4	0 set
3 fryers	6	□ set
4 fryers	8	1 set
5 fryers	8	1 □ set
6 fryers	8	2 set

Filtronic II Filter Systems (14" □nd 18"): No c□sters □re included with these systems. Must order c□sters □nd specify swivel or st□tion□ry. On systems with 2 or more fryers, we recommend □ll swivel c□sters. Ple□se specify loc□tion of filter system. On 4 or more fryers, we recommend loc□ting filter under the 2 middle fryers.
Loc□tion of filter system does □lter c□ster requirements. See □ppropri□te ch□rt below.

Filtronic II **14"** Filter Systems
Filter loc□ted on the **left or right**

No. of fryers	Tot□l number of c□sters on system	***Add to order**
2 fryers	4	1 set
3 fryers	4	1 set
4 fryers	6	1 □ sets
5 fryers	6	1 □ sets
6 fryers	8	2 sets

Filtronic II **18"** Filter Systems
Filter loc□ted on the **left or right**

No. of fryers	Tot□l number of c□sters on system	***Add to order**
2 fryers	4	1 set
3 fryers	6	1 □ sets
4 fryers	6	1 □ sets
5 fryers	6	1 □ sets
6 fryers	8	2 sets

Filtronic II **14" □nd 18"** systems
Filter loc□ted in the **center**

No. of fryers	Tot□l number of c□sters on system	***Add to order**
2 fryers	8	2 sets
3 fryers	8	2 sets
4 fryers	8	2 sets
5 fryers	8	2 sets
6 fryers	8	2 sets

G□s Connections:

14VFS □"
1 fryers □"
2-4 fryers 1"
(up to 500,000 BTU per m□nifold)
5-6 fryers 1 □"
Note: (Do not stock 1 □")

IMPORTANT: B□nk jobs of 5-6 fryers will ship in two sections.